AMERICAN REFINING GROUP INC. MATERIAL SAFETY DATA SHEET

BRAD PENN® PENN-GRADE 1ä PART PRODUCT CODE: BP-7119

BRAD PENN® PENN-GRADE 1ä PART SYNTHETIC RACING OIL SAE 20W-50

NFPA HAZARD RATING

4 – Extreme 3 – High 2 – Moderate

1 - Insignificant

PRODUCT NFPA HAZARD RATING

Health – 0
Fire – 1
Reactivity - 0

PAGE 1

DIVISION AND LOCATION---SECTION I

<u>Division:</u> LUBRICANTS AND SPECIALTY PRODUCTS DIVISION

Location: BRADFORD, PENNSYLVANIA

77 N. KENDALL AVE, BRADFORD, PA 16701

Emergency Telephone Number: (814) 368-1297

Transportation Emergency: CHEMTREC 1-(800) 424-9300 (U.S. AND Canada)

CHEMICAL AND PHYSICAL PROPERTIES --- SECTION II

.....

Chemical Name: petroleum hydrocarbon plus additives

Formula: not applicable

Hazardous Decomposition Products:

carbon monoxide and carbon dioxide from burning.

Incompatibility (Keep away from):

strong oxidizers such as hydrogen peroxide, bromine, and chromic acid.

| Product Components | <u>CAS No.</u> | <u>% (Volume)</u> |
|---|----------------|-------------------|
| Solvent Refined Heavy Paraffinic Distillate | 64741-88-4 | 40-50 |
| Solvent Refined Residual Oil | 64742-01-4 | 15-25 |
| Synthetic Hydrocarbon Base Oil | Mixture | 10-20 |
| Additives | Mixture | 20-25 |

Form: liquid Odor: motor oil Appearance: liquid Color: green

Specific Gravity (water=1): .0.88

Boiling Point: greater than 330°C (625°F)

Pour Point: less than -33°C (-27°F)

Solubility in Water (by weight %): 0 at 20°C

Evaporation Rate: not determined Vapor Pressure (mm Hg at 20°C): 0 Vapor Density (air=1): not volatile

pH (as is): not applicable

<u>Stability:</u> Product is stable under normal conditions Viscosity SUS at 100°F: Greater than or = to 100

(Continued on next page)

AMERICAN REFINING GROUP INC. MATERIAL SAFETY DATA SHEET

BRAD PENN® PENN-GRADE 1ä PART SYNTHETIC RACING OIL SAE 20W-50

SYNTHETIC RACING OIL SAE 20W-50 PAGE 2

FIRE AND EXPLOSION DATA---SECTION III

Special Fire Fighting Procedures:

Do not use water except as fog.

<u>Unusual Fire and Explosion Hazards:</u>

Do not cut, weld, braze, solder, drill, grind or expose containers, drums, tanks, etc. of product to heat, flame, sparks, static electricity or other sources of ignition; they may ignite explosively.

PRODUCT CODE: BP-7119

Flashpoint: (Method Used) Cleveland open cup greater than 216°C (420°F)

Flammable limits %: not applicable

Extinguishing accents:

Drychemical or Waterfog or C02 or Foam

Closed containers exposed to fire may be cooled with water.

.....

HEALTH HAZARD DATA---SECTION IV

Permissible concentrations (air):

see COMMENTS section

Chronic effects of overexposure:

no data available

Acute toxicological properties:

no data available

Emergency First Aid Procedures:

Eyes: Immediately flush with large quantities of water for at least 15 minutes and call a

physician.

Skin Contact: Remove excess with cloth or paper. Wash thoroughly with soap and water.

Inhalation: Remove victim to fresh air. Call a physician.

If Swallowed: Contact a physician immediately.

.....

SPECIAL PROTECTION INFORMATION---SECTION V

Ventilation Type Required (Local, mechanical, special):

see COMMENTS section

Respiratory Protection (Specify type):

Use NIOSH/MSHA certified respirator with dual organic vapor/mist and particulates cartridge if vapor concentration exceeds permissible exposure limit.

Protective Gloves:

neoprene type

Eve Protection:

chemical safety goggles

Other Protective Equipment:

none

(Continued on next page)

AMERICAN REFINING GROUP INC.

| BRAD PENN® PENN-GRADE 1ä PART SYNTHETIC RACING OIL SAE 20W-50 | PRODUCT CODE: BP-7119 PAGE 3 |
|--|--|
| HANDLING OF SPILLS OR LEAKSSECTION VI | |
| Procedures for Clean-Up: Transfer bulk of mixture into another container. Absorb sand, or vermiculite. Sweep up and dispose as solid w regulations. Waste Disposal: Dispose of in accordance with all applicable federal, sta | aste in accordance with local, state, ar |
| SPECIAL PRECAUTIONSSECTION VII | |
| Precautions to be taken in handling and storage: Do not handle or store at temperatures over Maximum Storage Temperature : 60 ° C (140°F) | |
| TRANSPORTATION DATASECTION VIII | |
| D.O.T.: Not Regulated Reportable Quantity: not applicable Freight Classification: Petroleum Lubricating Oil Special Transportation Notes: None | |
| ENVIRONMENTAL/SAFETY REGULATIONS—SECTION IX | |
| Section 313 (Title III Superfund Amendment and Reauthorization Act): | |
| This product contains the following toxic chemical categoreporting requirements of Section 313 of Title III of the Seauthorization Act of 1998 and 40 CFR Part 372 (per 1.2% zinc compound | Superfund Amendments and |

COMMENTS

If used in applications where a mist may be generated, observe a TWA/PEL of 5 mg/m3 for mineral oil mist (OSHA and ACGIH).

All components of this product are on the US TSCA Inventory and Canadian Domestic Substance List..

The additive mixtures in this product have been declared a trade secret by the additive manufacturers.

(Continued on next page)

AMERICAN REFINING GROUP INC. MATERIAL SAFETY DATA SHEET

BRAD PENN® PENN-GRADE 1ä PART SYNTHETIC RACING OIL SAE 20W-50

SYNTHETIC RACING OIL SAE 20W-50 PAGE 4

PRODUCT CODE: BP-7119

Prepared by: Monica C Mathers
Title: Product Steward Leader

Original Date: 06/27/01 Revision Date: 03/29/07 Supersedes: 12/21/04

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.